

HL0606.1E

cast iron grate 226x226mm



TECHNICAL DATA

material	Gusseisen	installation height	
dimension	226x226mm	grate frame	
capacity		grate	
weight	6,046	load class	B - 12,5t
EAN	9003076060610	inlet	
		standards	

MAIN DATA

used with



HL605
perfect-drain DN110 horizontal 244x244mm plastic /226x226mm cast iron with frost-proof flap seal



HL605.1
perfect-drain DN110 horizontal 260x260mm/226x226mm cast iron with frost-proof flap seal



HL605.1W
perfect-drain DN110 horizontal 260x260mm/226x226mm cast iron with trap seal



HL605W
perfect-drain DN110 horizontal 244x244mm plastic/226x226mm cast iron with trap seal

**HL606.1/1**

Perfect-drain DN110 vertical 260x260mm/226x226mm cast iron with frost-proof flap seal

**HL606.1/5**

perfect-drain DN160 vertical 260x260mm/226x226mm cast iron with frost-proof flap seal

**HL606.1W/1**

perfect-drain DN110 vertical 260x260mm/226x226mm cast iron with trap seal

**HL606.1W/5**

perfect-drain DN160 vertical 260x260mm/226x226mm cast iron with trap seal

**HL606/1**

perfect-drain DN110 vertical 244x244mm plastic/226x226mm cast iron with frost-proof flap seal

**HL606/5**

perfect-drain DN160 vertical 244x244mm plastic/226x226mm cast iron with frost-proof flap seal

**HL606W/1**

perfect-drain DN110 vertical 244x244mm plastic/226x226mm cast iron with trap seal

**HL606W/5**

perfect-drain DN160 vertical 244x244mm plastic/226x226mm cast iron with trap seal

**HL621**

Grating d 195mm/240x240mm/226x226mm cast iron

**HL615**

perfect-drain DN110 horizontal with flange, 240x240mm plastic/226x226mm cast iron with frost-proof flap seal

**HL615H**

perfect-drain DN110 horizontal with bitumen membrane, 240x240mm plastic/226x226mm cast iron with frost-proof flap seal

**HL615HW**

perfect-drain DN110 horizontal with bitumen membrane, 240x240mm plastic/226x226mm cast iron with trap seal

**HL615W**

perfect-drain DN110 horizontal with flange, 240x240mm plastic/226x226mm cast iron with trap seal

**HL616/1**

perfect-drain DN110 vertical with flange, 240x240mm plastic/226x226mm cast iron with frost-proof flap seal

**HL616/5**

perfect-drain DN160 vertical with flange, 240x240mm plastic/226x226mm cast iron with frost-proof flap seal

**HL616H/1**

perfect-drain DN110 vertical with bitumen membrane, 240x240mm plastic/226x226mm cast iron with frost-proof flap seal

**HL616H/5**

perfect-drain DN160 vertical with bitumen membrane, 240x240mm plastic/226x226mm cast iron with frost-proof flap seal

**HL616HW/1**

perfect-drain DN110 vertical with bitumen membrane, 240x240mm plastic/226x226mm cast iron with trap seal

**HL616HW/5**

perfect-drain DN160 vertical with bitumen membrane, 240x240mm plastic/226x226mm cast iron with trap seal

**HL616W/1**

Perfect-drain DN110 vertical with flange, 240x240mm plastic/226x226mm cast iron with trap seal

**HL616W/5**

Perfect-drain DN160 vertical with flange, 240x240mm plastic/226x226mm cast iron with trap seal

**HL624**

Grating d 195mm/cast iron frame 260x260mm/226x226mm cast iron

**HL615.1**

perfect-drain DN110 horizontal with flange, 260x260mm/226x226mm cast iron with frost-proof flap seal

**HL615.1H**

perfect-drain DN110 horizontal with bitumen membrane, 260x260mm/226x226mm cast iron with frost-proof flap seal

**HL615.1HW**

perfect-drain DN110 horizontal with bitumen membrane, 260x260mm/226x226mm cast iron with trap seal

**HL615.1W**

perfect-drain DN110 horizontal with flange, 260x260mm/226x226mm cast iron with trap seal

**HL616.1/1**

perfect-drain DN110 vertical with flange, 260x260mm/226x226mm cast iron with frost-proof flap seal

**HL616.1/5**

perfect-drain DN160 vertical with flange, 260x260mm/226x226mm cast iron with frost-proof flap seal

**HL616.1H/1**

perfect-drain DN110 vertical with bitumen membrane, 260x260mm/226x226mm cast iron with frost-proof flap seal

**HL616.1H/5**

perfect-drain DN160 vertical with bitumen membrane, 260x260mm/226x226mm cast iron with frost-proof flap seal

**HL616.1HW/1**

perfect-drain DN110 vertical with bitumen membrane, 260x260mm/226x226mm cast iron with trap seal

**HL616.1HW/5**

perfect-drain DN160 vertical with bitumen membrane, 260x260mm/226x226mm cast iron with trap seal

**HL616.1W/1**

perfect-drain DN110 vertical with flange, 260x260mm/226x226mm cast iron with trap seal

**HL616.1W/5**

perfect-drain DN160 vertical with flange, 260x260mm/226x226mm cast iron with trap seal

PACKAGING DATA**Euro-pallet**

unit	150 [pcs.]
weight	948,1 [kg]
EAN/pack.	
height/width/depth	555/800/1200 [mm]
volume	0,5328 [m ³]

DOWNLOADS

Foto Print	HL0606_1E_pr.tif	max.
Foto Web	HL0606_1E_B.jpg	640x480/300dpi
Foto Parts List	HL0606_1E_gr.jpg	150x150/72dpi